

ComColor FT Series



Ultra High-Speed
Full-Color Inkjet Printers



A feature-rich lineup for
**NATURE-
FRIENDLY,**

ULTRA-FAST
full-color printing

High environmental performance, high efficiency

Where environmental friendliness

Cleaner and Friendlier

RISO's environmental ethos is—and always has been—to design and develop products that exert the smallest possible impact on the environment throughout their lifecycles.

Low energy consumption

- Operates on standard power
- Does not generate heat like toner printers

360w
(During printing)

Virtually no harmful emissions

- Low volumes of VOCs*
- No toner particle emissions

**Generates virtually
no ozone**

Low resource consumption

- High-durability design means few replacement parts
- Inkjet printers do not require consumables (drum, fuser unit, etc.) like toner printers

Less waste

Low TEC** value

- Low energy consumption even during continuous high-speed printing
- Energy efficiency vastly superior to other printers operating at same speed

1.75kWh/week



BLUE ANGEL

German government-operated certification awarded to products and services meeting stringent requirements for sustainable consumption.



ENERGY STAR®

US-based voluntary program promoting energy efficiency. Strict energy-saving criteria must be satisfied to earn certification.

*VOCs: Volatile organic compounds.

**TEC value: Typical Electricity Consumption. This value represents electricity consumed in one week, and is based on the international ENERGY STAR standard. The TEC value is the value published on the ENERGY STAR website.

Values on these pages are specifications of the ComColor FT5430.

and productivity unite.

Smarter and Faster

Enjoy enhanced time efficiency, optimized TCO, and consistently high quality that only RISO can deliver.



High speed, high productivity

- First print time of less than 5 seconds
- 1,000 sheets in only 7 minutes

140ppm
(A4LEF)

High reliability

- Simple inkjet mechanism is durable and requires few replacement parts
- Low maintenance

**Less
downtime**

High usability

- Intuitively designed user interface
- 90-degree tilt panel for easy viewing

**Simple
operation**



EPEAT Gold

EPEAT is a US-based rating system. EPEAT Gold is the highest of three levels of sustainable performance.



ECO MARK


Japan-based environmental certification awarded to products featuring low environmental loading throughout the product lifecycle.

This can only be acquired by Japan models.

Lower and Higher

Heatless printing process

RISO's proprietary technology features in-line Piezo inkjet print heads which make possible single-pass full-color printing without generating heat.



Stationary print heads

Stationary print heads make possible stable, high-quality printing even at high speeds. And the simple paper feed mechanism enables printing on various types of paper.

Reduces energy, emissions

RISO inkjet printers do not generate heat during printing, nor do they generate ozone like toner printers.

Increases speed, efficiency

Oil-based ink is fast drying so paper doesn't curl, allowing you to move quickly to post-print processes.

High cost efficiency

- Proprietary ink and color profile development enable high quality at low running cost
- Short printing time means reduced labor and electricity costs

Low running cost

High image quality

- Piezo drop-on-demand print heads
- Fast-drying oil-based ink for minimal bleeding and smearing
- New, higher black density improves visibility

Enhanced visibility and color reproduction

High media flexibility

- 46gsm-400gsm
(when optional accessories attached)

Lightweight to heavyweight paper, as well as envelopes

Why inkjet?

Inkjet printing is more nature-friendly than laser printing, and still delivers excellent quality when printing in full color. And RISO technologies have also supported the advancement of high-volume industrial printing.

Why oil-based pigment ink?

It offers superior fading and water resistance, as well as strong resistance to bleeding. And, as it is fast-drying, paper rarely gets dirty or rippled – even during high-speed printing – enabling smooth high-speed duplex printing and transition to post-print processes.



Oil-based pigment ink enables flat, cold, dry output.



Water-based inks are prone to deformation such as rippling and curling.

ComColor standard – high color quality

RISO developed its own intelligent color profile to maximize color reproduction and minimize bleeding. ComColor Standard assesses the color data and paper type, and adjusts the volume of ink applied based on the paper's absorption characteristics.

Richer and Fuller





ComColor FT Series inkjet printers offer the complete package of industry-leading environmental friendliness and productivity, cost performance, and amazing functionality. And attaching the optional accessories available further enhances productivity and convenience. They're ideal high-speed, full-color printing solutions for all sizes and scales of operations, from small offices to in-plant applications. In-plant facilities are often tasked with fulfilling the needs of multiple departments and organizations, and ComColor FT Series printers, with blazing speed, gorgeous color reproduction, long duty cycles, and many sophisticated finishing options can satisfy the needs of various sizes of enterprises.

FT Series optional accessories



Multifunction Finisher

With its intelligent design and automatic execution, the Multifunction Finisher makes finishing processes such as stapling, punching, folding, and booklet making easier and more efficient than ever before.



High processing speed

- Keeps pace with FT Series high printing speed

140ppm* (A4LEF)

Low power consumption

- High productivity, high efficiency
- Only uses 230W (without Folder Unit)

590w* (in combination with FT main unit)

*When attached to the ComColor FT5430

The RISO way to enjoy nature

Additional Sheet Feeder

- Paper is replenishable even during printing
- Easy access and loading
- Max. 4,000 sheets in combination with paper feed tray provided with FT main unit

2,000 sheets



Face Down Finisher

- ComColor finisher exclusively for offset stacking and stapling finished prints



Staple



Offset stacking

Compact size,
simple operation



High-speed HS7000 Scanner

- Scan sizes up to A3
- Simultaneous duplex scanning
- Compatible with various file formats (PDF, PDF/A, TIFF, JPEG)

100ppm (A4LEF)

Postscript RIP for higher productivity

- Compatible with transactional printing
 - Queue settings
 - Tray selection per page
 - Form overlay

Intelligent automation
with Postscript RIP

-friendly, ultra-fast printing

ComColor FT5430 Specifications

Ink Type	Oil-based pigment ink (Cyan, Magenta, Yellow, Black)		
Print Resolution	Standard: 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction) Fine: 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)		
Continuous Print Speed	A4 Long-edge Feed	Simplex: 140 ppm	Duplex: 70 sheets/minute (140ppm)
	A3 Short-edge Feed	Simplex: 79 ppm	Duplex: 39 sheets/minute (78ppm)
Paper Size	Standard Tray	Maximum: 340 mm × 550 mm	Minimum: 90 mm × 148 mm
	Feed Tray	Maximum: 297 mm × 432 mm	Minimum: 182 mm × 182 mm
Paper Weight	Standard Tray	Simplex: 46 gsm to 210 gsm Duplex: 46 gsm to 210 gsm for A4 / 46 gsm to 104 gsm for A3, B4 (JIS)	
	Feed Tray	Simplex/Duplex: 52 gsm to 104 gsm	
Power Source	AC 100-240 V, 10.0-5.0 A, 50-60 Hz		
Power Consumption	Max. 1,000 W Ready: 95 W or less Sleep: 2 W or less Stand-by: 0.4 W or less		
Dimensions (W × D × H)	In use: 1,030 mm × 735 mm × 1,115 mm With cover and tray closed: 775 mm × 710 mm × 970 mm		
Weight	Approx. 137 kg		

For more detailed specifications on the FT5430 and the FT Series, please refer to the corresponding leaflet.

ComColor FT Series Optional Accessory Specifications

Scanner HS7000	Maximum Scanning Area		When using platen glass: 303 mm × 432 mm	When using ADF: 295 mm × 430 mm	
	Copy Functions	Writing Resolution	Standard: 300 dpi × 300 dpi	Fine: 300 dpi × 600 dpi	
		Copy Paper Size	Maximum: 303 mm × 432 mm		
		First Copy Time	7 sec. or less (when copying A4-LEF orientation using Color Priority Mode)		
	ADF	Scanning Speed	70 ppm or higher (Simplex/Duplex copying A4-LEF, using ADF)		
		Reproduction Size	50% to 200% (Copy mode)		
		Original Size	Maximum: 297 mm × 432 mm	Minimum: 100 mm × 148 mm	
		Paper Weight	52 gsm to 128 gsm		
		Original Capacity	Max. 200 sheets, Height up to 25 mm		
	Scan Functions	Scanning Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi		
		Scanning Speed	100 ppm (A4-LEF, 300 dpi)		
		Network Interface	Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T		
		Data-saving Method	Save to main unit hard drive, server, or USB flash drive, or send by e-mail		
		Data-saving Format	Monochrome: TIFF, PDF, PDF/A Grayscale/Full Color: TIFF, JPEG, PDF, PDF/A		
Power Source / Power Consumption		AC 100-240 V, 1.2-0.6 A, 50-60 Hz / Max. 100 W			
Dimensions (W × D × H)	640 mm × 560 mm × 255 mm				
Weight	Approx. 25 kg				
Additional 2000 Sheet Feeder FG20	Applicable Paper Size	A4-LEF, B5 (JIS)-LEF			
	Paper Weight	52 gsm to 104 gsm			
	Tray Capacity	Height up to 220 mm			
	Power Source	Power supplied from the main unit			
	Dimensions (W × D × H)	415 mm × 600 mm × 390 mm			
Weight	Approx. 29 kg				
Face Down Finisher F10	Applicable Paper Size	Without Offset	Maximum: 340 mm × 550 mm	Minimum: 90 mm × 148 mm	
		Offset Output	Regular sized paper width: 182 mm × 257 mm - 297 mm × 431.8 mm	Irregular sized paper width: 131 mm × 148 mm - 305 mm × 550 mm	
	Paper Weight	46 gsm to 210 gsm			
	Tray Capacity	Height up to 108 mm			
	Maximum Number of Sheets for Staples	50 sheets (85 gsm): A4, A4-LEF, B5 (JIS), B5 (JIS)-LEF 25 sheets (85 gsm): A3, B4 (JIS)			
	Paper Weight for Staples	52 gsm to 210 gsm			
	Staple Position	1 at front side (angle stapling), 1 at rear side (angle stapling), 2 at center (parallel stapling)			
	Power Source / Power Consumption	AC 100-240 V, 1.1-0.5 A, 50-60 Hz / Max. 100 W			
Dimensions (W × D × H)	635 mm × 695 mm × 580 mm				
Weight	Approx. 35 kg				
Multifunction Finisher FG20	Applicable Paper Size	Top Tray	Maximum: 330 mm × 488 mm (Duplex: 460 mm)	Minimum: 100 mm × 148 mm	
		Stacking Tray	Maximum: 330 mm × 488 mm (Duplex: 460 mm)	Minimum: 148 mm × 148 mm	
		Stapling	Maximum: 297 mm × 432 mm	Minimum: 182 mm × 148 mm	
		Booklet Tray	Maximum: 330 mm × 460 mm	Minimum: 182 mm × 257 mm	
	Paper Weight	Top Tray / Stacking Tray	52 gsm to 210 gsm		
		Booklet Tray	60 gsm to 90 gsm Cover pages: 90 gsm to 210 gsm		
	Stapling	Maximum Number of Staples	100 sheets (85 gsm)		
		Staple Position	1 at front side (angle stapling, parallel stapling), 1 at rear side (angle stapling, parallel stapling), 2 at center (parallel stapling)		
	Punching	Number of Punches	2 holes, 4 holes		
		Paper Size	2 holes: A3, B4 (JIS), A4-LEF, A4, B5 (JIS)-LEF 4 holes: A3, A4-LEF		
	Creating a Booklet	Paper Weight	52 gsm to 210 gsm		
Maximum Number of Sheets		Center margin: 20 sheets (85 gsm) 80 pages 2-fold: 5 sheets (85 gsm) 20 pages			
Power Source	AC 100-240 V, 50-60 Hz, 2.3-1.1 A (3.0-1.5 A with Folder Unit)				
Power Consumption	Max. 230 W (300 W with Folder Unit)				
Dimensions (W × D × H)	1,205 mm (1,440 mm with Folder Unit [235 mm]) × 735 mm × 1,215 mm				
Weight	Approx. 146 kg (198 kg with Folder Unit [52 kg])				
ComColorExpress RS1200C	Page Description Language	PostScript® Level 3 (CPSI: 3019), PDF (1.7), PCL 5c, PCL 6 (PCL XL), TIFF (6.0), PPML (2.1)			
	Applicable Protocol	TCP/IP, HTTP, HTTPS (TLS), DHCP, FTP, SMBv3, NetBIOS, LPR, IPP, Port 9100 (RAW port), IPv4, IPv6, IPsec (IKEv1)			
PS Kit FG10	Installed Fonts	PS: 139 fonts (Type 1: 120, TrueType: 19) PCL: 80 fonts			
	Page Description Language	PostScript Level 3 (CPSI: 3019), PDF (1.7), PCL 5c, PCL 6 (PCL XL), TIFF (6.0)			
RISO Auto-Control Stacking Tray II	Applicable Protocol	TCP/IP, HTTP, HTTPS (TLS), DHCP, FTP, LPR, IPP, SNMP (SNMPv1), Port 9100 (RAW port), IPv4, IPv6, IPsec (IKEv1)			
	Installed Fonts	PS: 136 Roman fonts and 2 Japanese fonts PCL: 88 Roman fonts			
Wide Stacking Tray	Paper Size	Maximum: 320 mm × 432 mm	Minimum: 90 mm × 148 mm		
	Tray Capacity	1,000 sheets (85 gsm)			
Envelope Feed Kit	Paper Size	Maximum: 340 mm × 550 mm	Minimum: 90 mm × 148 mm		
	Tray Capacity	1,000 sheets (85 gsm)			
Card Feed Kit	Paper Size	Maximum: 270 mm × 382 mm	Minimum: 90 mm × 148 mm		
	Paper Weight	50 gsm to 120 gsm			
Card Feed Kit	Paper Size	Maximum: 160 mm × 218 mm	Minimum: 100 mm × 148 mm		
	Paper Weight	100 gsm to 400 gsm			

Specifications are subject to change without notice.



ComColor FT Ink Cartridges

Colors: Black, Cyan, Magenta, Yellow

© RISO, ComColor, and FORCEJET are trademarks or registered trademarks of RISO KAGAKU CORPORATION. Adobe and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.



RISO KAGAKU CORPORATION
5-34-7 Shiba, Minato-ku, Tokyo 108-8385 Japan
<https://www.riso.com/>